

Product

KRB 0560



KRB-0560 is a crimping tool for non insulated connectors 6.3 mm, 0.5 - 6 mm²/.250", AWG 22-10, B/F-Crimp. Short and long handle available.

- High strength, through hardened alloy steel construction
- · Unique mechanism significantly reduces hand force requirement over competing crimping tools
- · Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- · Full cycle crimp mechanism to ensure consistent, reliable crimp
- · Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- · Hole in handle allows attachment of safety strap
- · Each tool has a unique serial number for traceability





Crimp profile

TECHNICAL DATA Length: 256 mm/10.08" Width: 22 mm/0.87" Height: 80 mm/3.15" Weight: 560 gr/1.23 lb

Wire size: 0.5-6 mm² / AWG 22-

AWG 10

Crimp dimensions mm/mm²: $0.5 - 1.5 \text{ mm}^2/1.5 - 2.5 \text{ mm}^2/4 - 6 \text{ mm}$

Crimp dimensions inch/AWG:

AWG 22 - AWG 16/AWG 16 - AWG 14/AWG 12 - AWG 10

Connector: Uninsulated open barrel connectors

Description: For uninsulated open

barrel connectors.

Life span, cycles: 50,000