


Product

# KRS 1560L-4



KRS-1560L-4 is a crimping tool for Solar connectors like MC4™ and similar connectors, Ø 4 mm/.157", with openbarrel conductor crimp 1.5 - 2.5, 4.0, 6.0 mm<sup>2</sup>/AWG 16 - 14, 12, 10. This tool also exist in versions for MC3™ and SOLARLOK™ connectors. (MC3™ and MC4™ are trademarks owned by Multi-Holding AG, Switzerland. SOLARLOK™ is a trademark owned by TE Connectivity, USA)



Die profile



Crimp profile

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability

#### TECHNICAL DATA

**Length:** 256 mm/10.08"

**Width:** 22 mm/0.87"

**Height:** 80 mm/3.15"

**Weight:** 642 gr/1.42 lb

**Wire size:** 1.5-6 mm<sup>2</sup> / AWG 16-AWG 10

**Crimp dimensions mm/mm<sup>2</sup>:**  
1,5 - 2,5 mm<sup>2</sup>/4 mm<sup>2</sup>/6 mm<sup>2</sup>

**Crimp dimensions inch/AWG:**  
AWG 16 - 14/AWG 12/AWG 10

**Connector:** Uninsulated open barrel connectors

**Description:** For Solar connectors like MC4™ and similar connectors, Ø 4 mm/.157 inch

**Life span, cycles:** 50,000